

## H.264 Real-Time DVR with 5.6" LCD Monitor - 4 Channel

### Features:

- H.264 compression chip, cost-effective, DSP format
- Built-in 5.6 inch TFT-LCD monitor
- Pentaplex operational mode : Recording, playback, remote viewing, back up, live viewing, simultaneously
- Support 4-ch playback simultaneously
- Support SATA Hard Disk, up to 1pcs
- Live view resolution / resource  
NTSC : 720 x 480 @ 120fps  
PAL : 704 x 576 @ 100fps
- Recording resolution / resource  
Real time mode  
NTSC : 360 x 240 @ 120fps  
PAL : 352 x 288 @ 100fps
- 4-Ch video input and 1-Ch video output
- 4-Ch audio input and 1-Ch audio output
- 4 suits of alarm inputs and 3 suits of alarm outputs
- Supports USB mouse
- RS-485 port for Pan / Tilt / Zoom control
- Playback: Channel selectable by single touch button during playback
- Remote view through IE browser or free bundle multi-client software

# RECON 4



### Specifications:

System			
Processor	High performance embedded microprocessor	Operating System	Embedded LINUX
Video			
Video Input	4 channel, BNC, 1.0Vp-p, 75Ω	Video Output	1 channel TV output, BNC 1 channel VGA output
Video Standards	NTSC (525Lines, 60Hz) PAL (625Lines, 50Hz)	Video Compression	H.264
Video Resolution	NTSC : 720 x 480 @ 120fps PAL : 704 x 576 @ 100fps	Recording Resolution / Resource	NTSC : 360 x 240 @ 120fps PAL : 352 x 288 @ 100fps
Video Display Split	1, 4	Image Quality	1 ~ 6 level (level 6 is the best)
Tour Display	Support	Video Information	Camera title, time, video loss, motion detection, recording
Camera Adjustment	Adjust color according to different time period	Privacy Masking	Self-defined four-side zone for privacy masking for each camera
Audio			
Audio Compression	ADPCM	Audio Input	4 channel
Audio Output	1 channel		

# H.264 Real-Time DVR with 5.6" LCD Monitor - 4 Channel

## Specifications:

<b>Video Detection &amp; Alarm</b>			
Motion Detection	192 areas	Video Loss	Trigger recording, alarm
Alarm Input	4 channel	Relay Output	3 channel
<b>Record, Playback &amp; Backup</b>			
Recording Mode	Manual, continuous, MD, alarm, schedule	Recording Priority	Manual>alarm>MD> continuous
Recording Interval	1 to 120 min. (default : 60min)	Playback	4 channel playback simultaneously
Search Mode	Time/Date, Alarm, MD	Backup Mode	Flash stick, USB HDD, USB CD-RW, USB DVD-RW, Network
<b>Network</b>			
Interface	RJ-45 port (10/100M)	Network Function	TCP/IP, DHCP
Remote operation	Monitor, PTZ control, playback, system setting, file download, log information		
<b>Auxiliary Interface</b>			
USB interface	2 ports	RS-232	PC communication
RS-485	Pan/Tilt/Zoom control		
<b>Environment</b>			
Power Supply	115V 60HZ / 230V 50Hz	Power Consumption	25W
Working Temperature	-10℃ ~ +55℃	Working Humidity	10% ~ 90%
Atmosphere Pressure	86kpa ~ 106kpa		

## Package Contains

- DVR x 1
- Power cable x 1
- Ethernet cable x 1
- Alarm & relay terminal blocks x 1
- Remote control x 1
- USB mouse x 1
- Accessories x 1
- User manual x 1
- CD-ROM (included PSS software..) x 1



5327 Cedar Creek Drive, Kemp, Texas 75143  
866-301-CCTV ~ 903-498-3240 ~ 903-498-8989  
sales@rugged-cctv.com ~ www.rugged-cctv.com